

Anilox Cleaning Gel

Ecological Cleaning Gel for dissolving dried Inkand Coating emulsions on Anilox cylinders

Key benefits

- efficiently removes dried ink and/or coating emulsion and restores maximum transfer capacity
- · suitable for cleaning both water- and solvent based residues
- · very efficient on AnicolorTM inking unit

Properties

- · biodegradable water based gel
- · use for manual cleaning or in an ultrasonic bath
- Colourless

Application

- apply undiluted to the cylinder using a firm bristle brush
- · make sure the full surface is covered with thick layer of gel
- let react for minimum 15 minutes, brush the surface again to reactivate
- repeat this procedure once more after minimum 15 minutes.
- rinse away carefully with fresh water, or preferably with 1/3 mixture Saphira
 Coating Cleaner 590 and water for enhanced performance

Technical Specifications

| Sheetfed | applicable |
|-----------|----------------|
| Heatset | not applicable |
| Coldset | not applicable |
| Flexo | applicable |
| Packaging | 1 L |

This technical data sheet is to inform and advice our customers. The successful application depends on variety of different factors which are beyond our control. We therefore ask for your understanding that these advice documents cannot be used as the basis for claims in law.

Heidelberger Druckmaschinen AG

Kurfürsten-Anlage 52-60, 69115 Heidelberg

Phone +49 6221 92-00, Fax +49 6221 92-6999, www.heidelberg.com

Trademarks

Heidelberg, the Heidelberg logotype and Saphira are registered trademarks of Heidelberger Druckmaschinen AG in the U.S. and other countries.

Subject to technical and other changes.